

cartridges with standard flat seals.

Housings DP BIG fit to 4.25" and 4.50" SX (DOE) cartridges.

Atlas Filtri BIG filter cartridges are availabe in a wide range of polypropylene wound thread models, single and multi-layer, and in a wide range of carbon block models as CTO, VOC, Pb, Cyst.

Housings DP S BIG with discharge valve are provided with a drain funnel to protect potable water from pollution by back-flow, in compliance with UNI EN 1717-11/2002.



Corporate Headquarters 259 South Main Street Middleton, MA 01949 (800) 539-1100

www.h2ocare.com

The products are tested and certified under the most stringent procedures worldwide, in compliance with DM 25 (Italy) and GOST (Russia).



DP BIG 10 max working pressure _8 bar (116 psi) DP BIG 20 max working pressure_ _7 bar (101 psi) 45°C (113°F) Max working temperature Min working temperature 4°C (39,2°F)



DRAIN FUNNEL Back-flow preventing device UNI EN 1717-11/2002

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Head: reinforced polypropylene.

Clear bowl: SAN.

Blue bowl: reinforced polypropylene.

O-ring: EPDM.

Breather-valve: body polypropylene, o-ring EPDM. Manometers: radial type, pressure range 0-12 bar, 0-170 psi. Discharge ball-valve: CW 617 N brass nickel plated. Discharge plastic nipple: reinforced polypropylene.

Drain funnel: reinforced polypropylene.



The new range of DP BIG housings is designed to fit to "BIG" filter cartridges with outer diameter (OD) from 4" to 4.50", inner diameter (ID) 1.10", height at 10" and 20" with standard SX (DOE) configuration. With female IN/OUT connections at 1" and 1"1/2, with BSP or NPT plastic threads DP BIG housings are suitable for every domestic Point-of-Entry (POE) or every industrial application when heavy-duty performance is a must.

Besides the standard models, DP BIG are also available with features new to the market:

- M models with 2 manometers
- S models with discharge valve and self-cleaning performance. S models can be used with KIT AUTO for automatic flushing and self-cleaning.
- S M models with discharge-valve and 2 manometers.



ATLAS FILTRI® is a registered trade mark of ATLAS FILTRI srl. Unauthorized use of the registered trade mark is strictly forbidden and legally persecuted. Images and texts are property of ATLAS FILTRI srl, which reserves the rights to change products design and specification without prior notice.